



SUBMERSIBLE PUMPS

Насос	Ступени	Производительность								Мощность		Размеры, мм		Вес, кг	
		Г/мин	0	13.2	26.4	39.6	46.2	52.8	66.0						
		л/мин	0	1.0	2.0	3.0	3.5	4.0	5.0	6.0					
		м³/час	0	3.6	7.2	10.8	12.6	14.4	18.0	21.6					
л/сек	0	60	120	180	210	240	300	360	Л.с.	кВт	Насос	Двиг.	Насос	Двиг.	
6-CI50-014-05	5	52	51	50	46	43	37	25	10	3.0	2.2	648	729	26	47
6-CI50-014-06	6	62	61	60	56	52	45	29	12	4.0	3.0	691	759	28	50
6-CI50-014-07	7	72	71	70	65	60	52	34	14	5.0	3.7	734	759	30	52
6-CI50-014-08	8	82	81	80	74	69	60	39	16	5.0	3.7	777	759	32	52
6-CI50-014-09	9	92	91	90	83	77	67	44	18	6.0	4.5	820	789	35	56
6-CI50-014-10	10	103	101	100	93	86	75	49	21	6.0	4.5	863	789	37	56
6-CI50-014-11	11	113	111	110	102	95	82	54	23	7.5	5.5	906	829	39	58
6-CI50-014-12	12	123	121	120	111	103	89	59	25	7.5	5.5	949	829	42	58
6-CI50-014-13	13	133	131	130	121	112	97	64	27	10	7.5	992	939	44	66
6-CI50-014-14	14	144	142	140	130	120	104	69	29	10	7.5	1035	939	46	66
6-CI50-014-15	15	154	152	150	139	129	112	74	31	10.0	7.5	1078	939	49	66
6-CI50-014-16	16	164	162	160	148	138	119	78	33	10.0	7.5	1121	939	51	66
6-CI50-014-17	17	182	180	177	165	150	131	88	43	12.5	9.3	1164	999	53	71
6-CI50-014-18	18	193	190	188	175	159	139	94	45	12.5	9.3	1207	999	55	71
6-CI50-014-19	19	203	201	198	184	168	146	99	48	12.5	9.3	1250	999	58	71
6-CI50-014-20	20	214	212	208	194	177	154	104	50	12.5	9.3	1293	999	60	71
6-CI50-014-21	21	225	222	219	204	186	162	109	53	15.0	11.0	1486	1079	71	78
6-CI50-014-22	22	235	233	229	213	195	169	114	55	15.0	11.0	1529	1079	73	78
6-CI50-014-23	23	246	243	240	223	204	177	120	58	15.0	11.0	1572	1079	75	78
6-CI50-014-24	24	257	254	250	233	212	185	125	60	15.0	11.0	1615	1079	77	78
6-CI50-014-25	25	268	265	261	243	221	193	130	63	17.5	13.0	1658	1129	80	82
6-CI50-014-26	26	278	275	271	252	230	200	135	65	17.5	13.0	1701	1129	82	82
6-CI50-014-27	27	289	286	281	262	239	208	140	68	17.5	13.0	1744	1129	84	82
6-CI50-014-28	28	300	296	292	272	248	216	146	70	17.5	13.0	1787	1129	87	82
6-CI50-014-29	29	310	307	302	281	257	223	151	73	20.0	15.0	1830	1179	89	89
6-CI50-014-30	30	321	317	313	291	266	231	156	75	20.0	15.0	1873	1179	91	89
6-CI50-014-31	31	332	328	323	301	274	239	161	78	20.0	15.0	1966	1179	96	89
6-CI50-014-32	32	342	339	333	310	283	246	166	80	20.0	15.0	2009	1179	99	89
6-CI50-014-33	33	353	349	344	320	292	254	172	83	25.0	18.5	2052	1089	101	86
6-CI50-014-34	34	364	360	354	330	301	262	177	85	25.0	18.5	2095	1089	103	86
6-CI50-014-35	35	375	370	365	340	310	270	182	88	25.0	18.5	2138	1089	106	86
6-CI50-014-36	36	385	381	375	349	319	277	187	90	25.0	18.5	2181	1089	108	86
6-CI50-014-37	37	396	391	386	359	327	285	192	93	25.0	18.5	2224	1089	110	86
6-CI50-014-38	38	407	402	396	369	336	293	198	95	25.0	18.5	2267	1089	112	86
6-CI50-014-39	39	417	413	406	378	345	300	203	98	25.0	18.5	2310	1089	115	86
6-CI50-014-40	40	428	423	417	388	354	308	208	100	25.0	18.5	2353	1089	117	86
КПД [%]		0	33	55	63	64	63	56	32						

СЕРИЯ 6-CI50-014 (14 м³/час)

6" СКВАЖИННЫЙ НАСОС

50 Hz

ГИДРАВЛИЧЕСКАЯ ПРОИЗВОДИТЕЛЬНОСТЬ НАСОСОВ

ISO 9906

