



SUBMERSIBLE PUMPS

Насос	Ступени	Производительность										Мощность		Размеры, мм		Вес, кг	
		Г/мин	0	66	88	110	132	146	176	198	220						
		л/сек	0	5.0	6.7	8.3	10.0	11.1	13.3	15.0	16.7						
		м³/час	0	18.6	24.0	30.0	36.0	40.0	48.0	54.0	60.1						
л/мин	0	300.0	400.0	500.0	600.0	666.7	800.0	900.0	1000.0	Л.с.	кВт	Насос	Двиг.	Насос	Двиг.		
6-С150-038А-02	2	Напор [М]	23	21	20	19	18	18	15	11	7	4.0	3.0	529	759	21	50
6-С150-038А-03	3		34	31	30	29	27	26	22	17	11	6.0	4.5	634	789	27	56
6-С150-038А-04	4		45	41	40	38	37	35	29	23	14	7.5	5.5	739	829	33	58
6-С150-038А-05	5		57	51	50	48	46	44	36	28	18	10.0	7.5	844	939	39	66
6-С150-038А-06	6		68	62	59	57	55	53	44	34	21	12.5	9.3	949	999	44	71
6-С150-038А-07	7		79	72	69	67	64	61	51	39	25	15.0	11.0	1054	1079	50	78
6-С150-038А-08	8		90	82	79	76	73	70	58	45	28	15.0	11.0	1159	1079	56	78
6-С150-038А-09	9		102	92	89	86	82	79	65	51	32	17.5	13.0	1264	1129	61	82
6-С150-038А-10	10		113	103	99	95	91	88	73	56	35	20.0	15.0	1369	1179	67	89
6-С150-038А-11	11		124	113	109	105	100	96	80	62	39	20.0	15.0	1474	1179	73	89
6-С150-038А-12	12		136	123	119	114	110	105	87	68	42	25.0	18.5	1579	1089	78	86
6-С150-038А-13	13		147	133	129	124	119	114	94	73	46	30.0	22.0	1684	1159	84	90
6-С150-038А-14	14		158	144	139	133	128	123	102	79	49	30.0	22.0	1789	1159	90	90
6-С150-038А-15	15		170	154	149	143	137	131	109	84	53	30.0	22.0	1894	1159	96	90
КПД [%]			0.0	50.0	60.0	65.0	69.5	69.5	65.0	60.0	50.0						

СЕРИЯ 6-С150-038 (38 м³/час)

6" СКВАЖИННЫЙ НАСОС

50 Hz

ГИДРАВЛИЧЕСКАЯ ПРОИЗВОДИТЕЛЬНОСТЬ НАСОСОВ

ISO 9906

